

The C125



The 104



The C119



The C118



The 220



Manufacturer	Frigomat		Taylor		Frigomat		Frigomat		Taylor		
Applications	Low to medium overrun gelato		Low to medium overrun gelato		Low to medium overrun gelato		Low to medium overrun gelato		High overrun ice cream		
External dimensions	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	
	Width	19"	480	16 - 7/16"	418	17 - 3/8"	440	20 - 1/2"	520	18 - 7/16"	468
	Depth	20"	490	26 - 13/16"	681	31 - 7/8"	810	39 - 3/4"	1010	40 - 1/2"	1029
Height	12"	340	21 - 3/8"	542	49 - 1/2"	1260	56"	1420	56 - 1/2"	1435	
Power supply	220v AC 50hz - 13amp socket (single phase only)		220v AC 50hz - 13amp socket (single phase only)		220v Single phase - 32amp or 415v Three phase - 12amp/phase		415v AC 50hz - 15amp per phase (Three phase only)		220v Single phase - 32amp or 415v Three phase - 12amp/phase		
Cooling system	Air cooled only		Air cooled only		Air or water cooled		Air or water cooled		Air or water cooled		
Air clearance required	6" (152mm) on both sides		6" (152mm) on both sides		6" (152mm) on both sides and 12" (305mm) at the rear		6" (152mm) on both sides and 12" (305mm) at the rear		3" (76mm) on all sides		
Refrigeration BTU/hr	2,664 BTU/hr		2,500 BTU/hr		15,500 BTU/hr		16,500 BTU/hr		15,000 BTU/hr		
Beater motor	One, 1.84 Kw		One, 1.0 HP		One, 2.0 HP		One, two speed motor. 2.5 HP at low speed, 4 HP at high speed		One, 1.5 HP		
Weight	121 lbs / 55 Kg		165 lbs / 74.9 Kg		373 lbs / 169 Kg		540 lbs / 245 Kg		500 lbs / 226.8 Kg		
Hopper capacity	n/a		n/a		n/a		n/a		One, 9.5 litres		
Load capacity per cycle	1 - 2.2 Kg		2 Kg		2 - 4 Kg		2 - 6 Kg		4 - 11 Kg		
Approximate hourly production	10 Kg		10 Kg		20 Kg		30 Kg		47.5 Kg		
Approximate overrun	20 - 30 %		25 - 35 %		30 - 40 %		30 - 40 %		50 - 60 %		
Consistency regulaton system	Time		Time		Viscosity		Viscosity		Time / Temperature		
Cleaning interval	Daily, after every use		Daily, after every use		Daily, after every use		Daily, after every use		Daily, after every use		
Additional features	Freezing cycle with time setting Cyclic agitation mode for granita Saftey cut off magnetic lid Tank drain plug Stainless steel agitator with nylon scraper		Freezing cycle with time setting warning buzzer. "Knife door" for presentation. Stainles steel agitator with nylon scrapers. Loading funnel		Six different freezing cycles Magnetic saftey cut offs on door "Knife door" for presentation		Automatic freezing cycle Semi-automatic freezing cycle Two slush freezing cycles Two speed beater Rinse tap Adjustble height shelf "Knife door" for presentation Magnetic saftey cut offs on door		Automatic freezing cycle with time setting warning buzzer. Dispensing spout "Knife door" is optional extra Adjustable height shelf Steel agitator with nylon scrapers		