

The 430



The 428



The PH61



The 370



Applications	Shakes, smoothies, cocktails & slush		Shakes, smoothies, cocktails & slush		Thick shake		Smoothies, cocktails & slush	
Number of flavours	Single		Single		Four (3 syrup tanks)		Two	
External dimensions	in.	mm.	in.	mm.	in.	mm.	in.	mm.
Width	16 - 7/16"	448	13 - 1/2"	343	18 - 7/16"	468	14 - 3/16"	360
Depth	27 - 11/16"	699	32 - 1/2"	826	35 - 1/4"	895	18 - 1/2"	470
Height	27 - 1/2"	762	32 - 5/8"	829	59 - 1/2"	1511	27 - 1/4"	690
Power supply	220v AC 50hz - 13amp socket (single phase only)		220v AC 50hz - 13amp socket (single phase only)		220v Single phase - 32amp or 415v Three phase - 20amp/phase		220v AC 50hz - 13amp socket (single phase only)	
Cooling system	Air cooled only		Air cooled only		Air or water cooled		Air cooled only	
Air clearance required	3"(76mm) on both sides		6"(152mm) on both sides		6"(152mm) on both sides		6"(152mm) on all sides	
Refrigeration BTU/hr	4,000 BTU/hr		3,600 BTU/hr		11,000 BTU/hr		3,000 BTU/hr	
Beater motor	One, 0.25 HP		One, 0.5 HP		One, 1.0 HP		n/a	
Weight	176lbs / 979.8Kg		221lbs / 100.2Kg		608lbs / 275.8Kg		86lbs / 39Kg	
Gravity feed or pump	Gravity		Gravity		Pump		Gravity	
Hopper capacity	13.2 litres		18.9 litres		One, 18.9 litres		Two, 10 litres	
Barrel capacity	3.8 litres		6.6 litres		One, 6.6 litres		n/a	
Approximate output	24.0 litres per hour		34.1 litres per hour		102.3 litres per hour		33x 10oz portions per side per fill	
Approximate overrun	30 - 35 %		30 - 35 %		30 - 35 %		5%	
Indicator Lights	Mix low & mix out lights		Mix low & mix out lights		Mix low & mix out lights		n/a	
Illuminated display	No		Yes		No		Yes	
Cleaning interval	3 days		3 days		Up to 14 days (self pasteurising)		3 days for dairy / 7 days for frozen drinks	
External air filter	No		Yes		No		No	
Optional extras	Water cooled Flavorburst connection Graphic panel decals Panel spinner Countertop spinner		Flavorburst connection Panel spinner Countertop spinner		Water cooled Hopper locks		Continuous auto fill system	