

# C119

## Horizontal Batch Freezer



ITEM No. \_\_\_\_\_

### Model options:

- C119/1A Batch Freezer (single phase, air cooled)
- C119/1W Batch Freezer (single phase, water cooled)
- C119/3A Batch Freezer (three phase, air cooled)
- C119/3W Batch Freezer (three phase, water cooled)

### Standard equipment:

- 1x Starter kit sanitiser sachets
- 1x White cleaning bucket
- 1x Bottle glycerine food safe lubricant
- 1x Cleaning brushes
- 1x Replacement tune up kit
- 12 Months parts & labour warranty

### Optional extras:

- Preventative maintenance visit (call for details)

### Features:

The C119 is a professional batch freezer designed to produce high-quality frozen dessert products, ice creams and gelato in smaller quantities with a reduced investment making it the ideal machine for restaurants, small dessert parlours and cafés.

Manufactured in Italy for Taylor by Frigomat to ensure that European equipment quality and technology standards are met.

- ◆ **Batch Size** - Production from 2Kg to 4Kg per cycle.
- ◆ **Hourly Production** - 20-25Kg (approximately 4 to 5 batches per hour)
- ◆ **Electronic Control** - Six freezing programs:
  - ◆ Automatic freezing cycle to reach the ideal consistency (viscosity) according to the type and quantity of mix being frozen
  - ◆ Automatic freezing cycle 'PLUS' for a firmer product on dispense
  - ◆ Semi-automatic freezing cycle with timer control
  - ◆ Semi-automatic freezing cycle with consistency control
  - ◆ Slush cycle with consistency setting and continuous agitation
  - ◆ Slush cycle with timer control and cyclic agitation
- The C119 automatically switches into a consistency preservation cycle at the end of each freezing cycle to maintain the product until the operator is ready to dispense the product.
- ◆ **High Precision** - The electronic IES features a new consistency control system that further improves the precision during different working conditions.
- ◆ **Efficiency** - The C119 has a stainless steel beater frame with removable, sprung scrapers which actively scrape the cylinder walls ensuring even freezing whilst maintaining maximum efficiency.
- ◆ **Safety** - The hopper grid incorporates a magnetic interlock switch preventing the machine from operating with either the hopper grid open or the door removed. The door features an additional safety grid to prevent objects entering the freezing cylinder during operation preventing injury or damage.
- ◆ **Easy Installation** - The C119's single phase power option and air cooled design makes it the perfect solution for those with limited power capacity or without access to three phase power.

PLEASE NOTE - Hourly production values are for guidance purposes only and does not constitute any guarantee. Actual production capacity is dependent on ambient working conditions and the type of product being frozen.



**Taylor UK**  
Catering Equipment Specialists

Taylor UK (a division of HTG Trading Ltd)  
106 Claydon Business Park, Gt. Blakenham,  
Ipswich, Suffolk, IP6 0NL, United Kingdom  
0800 838 896 - sales@taylor-company.co.uk  
www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification - April 2020

C119 - Horizontal Batch Freezer - 2Kg to 4Kg


# C119





## Horizontal Batch Freezer

ITEM No. \_\_\_\_\_

Section view:



Taylor C119	SINGLE PHASE	THREE PHASE
External dimensions (WxDxH)	440 x 810 x 1260 mm	
Net weight	169 Kg	
Wall clearance* (sides/back/top)	150 / 300 / 150 mm	
Frigomat Batch Freezers are <b>NOT</b> designed for built-in installation		
Refrigeration system	8,300 BTU - R452a	
Beater motor (No./Power)	1 - 2.0 HP	
Cooling	Air or Water	
Cold water supply**	3/4" BSP (22mm) Ø	
Supply water temperature	13 -20 °C	
Supply water pressure	1-3 BAR (15-43 PSI)	
Waste water connection***	3/4" BSP (22mm) Ø	
Voltage	230v / 50Hz / 1Ph	400v / 50Hz / 3Ph
Nominal power	2.8 Kw / 15 amp	2.8 Kw / 6 amp/ph
Circuit breaker	24 amp	16 amp
Isolator socket	32 amp (1P+N+E) 	16 amp (3P+N+E) 

\*Minimum air clearances **MUST** be met to ensure adequate airflow for optimum performance of air cooled machines. Air cooled units should not have the back of the machine placed against the wall when in operation to allow the escape of warm air.

\*\*ALL machines require a water connection via a suitable WRAS approved inlet hose to a 15mm Mains 'Potable' water supply installed with a WRAS approved 'Check Valve', minimum 1 bar maximum 3 bar pressure, this prior to termination with 'washing machine style' stop valve to suit a 3/4BSP hose fitting. Hoses supplied with the machine are WRAS approved.

\*\*\*Water cooled machines will require a suitable waste water drain down pipe fitted with a U-bend.

•A dedicated power supply is required for safe operation. Taylor by Frigomat equipment should never be operated on any form of extension lead, please consult a qualified electrician for correct installation advice.

Data for air cooled units.



**Taylor UK** (a division of HTG Trading Ltd)  
106 Claydon Business Park, Gt. Blakenham,  
Ipswich, Suffolk, IP6 0NL, United Kingdom  
**0800 838 896 - sales@taylor-company.co.uk**  
**www.taylor-company.co.uk**

Due to continual research and development, these specifications are subject to change without notification - April 2020

C119 - Horizontal Batch Freezer - 2Kg to 4Kg