G20 Vertical Batch Freezer







Freezer door; closed, open, and disassembled



Freezing cylinder with beater and removable scrapers

PLEASE NOTE - Hourly production values are for guidance purposes only and does not constitute any guarantee. Actual production capacity is dependent on ambient working conditions and the type of product being frozen.





Taylor UK (a division of HTG Trading Ltd) 106 Claydon Business Park, Gt. Blakenham, Ipswich, Suffolk, IP6 ONL, United Kingdom 0800 838 896 - sales@taylor-company.co.uk www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification - April 2022

ITEM No.

Model options:

G20/3A Batch Freezer (three phase, air cooled)

Standard equipment:

- 1x Bottle glycerine food safe lubricant
- 1x Cleaning brush
- 1x Replacement tune up kit
- 12 Months parts & labour warranty

Optional extras: Preventative maintenance visit (call for details)

The G20 vertical batch freezer has been specifically designed for the easy production of quality gelato, ice cream and sorbet in batches suitable to fill the most popular standard container sizes. The traditional design makes the G20 extremely reliable, easy to use and maintain. This machine is ideal for both the experienced gelato master as well as for the beginner who has just started making their own frozen products.

Manufactured in Italy by Frigomat to ensure that European equipment quality and technology standards are met.

- Batch Size Production from 2.5 Kg to 4.5 Kg per cycle.
- Hourly Production 15-20 Kg (approximately 4 batches per hour)
 Controls

Controis

- Electromechanical Control -
- Freezing cycle with timer control
- End-cycle buzzer
- Multi-direction beater rotation; anti-clockwise when freezing, clock-wise for product extraction
- Two beater speeds; normal for freezing, high-speed for extraction


Features

- Freezing Cylinder The G20 features a vertical stainless steel freezing cylinder with a removable steel agitator which has removable nylon scrapers which actively push against the cylinder walls for greater efficiency. The freezing system works on both the bottom and cylinder walls to obtain the perfect consistency of the product.
- Lid The transparent polycarbonate lid allows easy inspection of the product during the freezing cycle. It features a 'safety cut-out' magnet which stops the agitation when the lid is lifted. This safety feature allows for the possibility to add small pieces nuts, dried fruits, candies and chocolate for 'stracciatella' during the later stages of the freezing process (Inclusions need to be small enough to pass through the safety grid on the dispense door).
- Door; practical and safe The G20 features a removable dispense door for easy cleaning which incorporates a safety grid to prevent objects entering the freezing cylinder during operation. The integrated magnetic safety cut out prevents the machine operating if the door is not installed correctly.

The wide extraction hole and 'knife' grid allows for quick extraction of the product whilst creating an artisan appearance.

• Easy - Mounted on castors, the G20 can be moved easily for cleaning purposes and the height adjustable stainless steel shelf allows for the uses of different size containers.

GZU - Vertical Batch Freezer - 2.5 Kg to 4.5 Kg



FRIGOMAT G20	THREE PHASE ONLY
External dimensions (WxDxH)	405 x 795 x 1080 mm
Net weight	130 Kg
Wall clearance* (right/back/left)	150 / 300 / 150 mm
Frigomat Batch Freezers are NOT designed for built-in installation	
Refrigeration system	1x ~1.400 W - R452A (@ -23.3°C evap. / +45°C cond.)
Beater motor (No./Power)	1 - 2.0 KW (2.7 HP)
Cooling	Air ONLY
Voltage	400v / 50Hz / 3Ph
Nominal power	2.6 KW / 6.5 amps/ph
Circuit breaker/fuse	16 amp
Isolator socket	16 amp (3P+N+E)

* Minimum air clearances MUST be met to ensure adequate airflow for optimum performance of air cooled machines. Air cooled units should not have the vent of the machine placed against the wall when in operation to allow the escape of warm air.
• A dedicated plug socket is required for safe operation. Frigomat equipment should never be operated on any form of extension lead, please consult a qualified electrician for correct installation advice.





Taylor UK (a division of HTG Trading Ltd) 106 Claydon Business Park, Gt. Blakenham, Ipswich, Suffolk, IP6 ONL, United Kingdom 0800 838 896 - sales@taylor-company.co.uk www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification - April 2022