

# C152

## Soft Serve Freezer - Single Flavour, Gravity



Taylor C152 with optional C208 cart



ITEM No. \_\_\_\_\_

### Model options:

- C152/1A Soft Serve Freezer
- C152/1A+C208 Soft Serve Freezer with optional cart

### Standard equipment:

- 1x Starter kit sanitiser sachets
- 1x White cleaning bucket
- 1x Tube Taylor foodsafe lubricant
- 1x Set Taylor cleaning brushes
- 1x Replacement tune up kit
- 12 Months parts & labour warranty

### Optional extras:

- 4" Legs
- Frozen yogurt spec mix feed tube
- Extended service contract (call for details)

### Features:

Offer all the popular soft serve variations from 'Whippy style' low or non-fat ice creams to custards, yogurt, sorbet and vegan desserts.

- ◆ **Freezing Cylinder** - One, 1.4 litre
- ◆ **Hourly Production\*\*** - 12.24 litres (approximately)
- ◆ **Mix Hopper** - One, 7.6 litre. Separate hopper refrigeration (SHR) maintains mix below 5°C in Auto and Standby modes.
- ◆ **Indicator Lights** - The Mix Low and Mix Out light alerts the operator to add mix. An audible alarm may be enabled to sound when mix is low.
- ◆ **Electronic Controls** - Softech™ is our exclusive microprocessor based master control that regulates refrigeration by measuring product viscosity to maintain consistent quality.
- ◆ **Standby** - During long no-use periods, the standby feature maintains safe product temperatures in the mix hopper and freezing cylinder.
- ◆ **Door Interlock System** - Protects the operator from injury as the beater will not operate without the dispensing door in place.



**Taylor UK**  
Catering Equipment Specialists

**Taylor UK** (a division of HTG Trading Ltd)  
106 Claydon Business Park, Gt. Blakenham,  
Ipswich, Suffolk, IP6 0NL, United Kingdom  
**0800 838 896 - sales@taylor-company.co.uk**  
**www.taylor-company.co.uk**

Due to continual research and development, these specifications are subject to change without notification - Jan 2020


# C152



## Soft Serve Freezer - Single flavour, gravity

ITEM No. \_\_\_\_\_

Section view: (Dimensions shown in brackets in mm)



Shown with optional C208 cart.

Taylor C152	SINGLE PHASE
External dimensions (WxDxH)	442 x 746 x 673 mm
External dimensions (WxDxH) on Cart	442 x 746 x 1354 mm
Net weight / crated weight (freezer only)	94 Kg / 108 Kg
Wall clearance* (sides/back)	150 mm / 0 mm
Soft serve freezers are <b>NOT</b> designed for built-in installation	
Refrigeration system - Main	3,000 BTU/hr
Refrigeration system - Hopper	400 BTU/hr
Beater motor (No./Power)	1 - 0.5 HP
Cooling	Air ONLY
Approximate hourly production**	12.24 ltr
Voltage	230v / 50Hz / 1Ph
Total amp draw	7.8 amps
Circuit breaker/fuse	13 amp
Isolator socket	13 amp (1P+N+E)



\*Minimum air clearances **MUST** be met to assure adequate airflow for optimum performance of air cooled machines. Place the back of the unit against a wall to prevent recirculation of warm air.  
 \*\*Hourly production figures are approximate and based on optimum operating conditions. Product type, ambient air temperature and air flow will effect the production capacity.  
 •A dedicated power supply is required for safe operation. Taylor equipment should never be operated on any form of extension lead, please consult a qualified electrician for correct installation advice.

C152 - Soft Serve Freezer - Single Flavour, Gravity



Data for air cooled units.



**Taylor UK** (a division of HTG Trading Ltd)  
 106 Claydon Business Park, Gt. Blakenham,  
 Ipswich, Suffolk, IP6 0NL, United Kingdom  
**0800 838 896 - sales@taylor-company.co.uk**  
**www.taylor-company.co.uk**

Due to continual research and development, these specifications are subject to change without notification - Jan 2020