DIVA PASTRY





March 2021

Due to continual research and development, these specifications are subject to change without notification.

DIVA PASTRY





Professional ventilated pastry display

Section view: (all dimensions in mm)

ITEM No.







H140

DIVA - PAS		Model type	Display area	Temp class	Reccom. temp	Energy class	Energy Efficiency	Annual Energy
Height	Length	type	m ²	61033	°C	61035	Index	kWh/A
H125	120	IHC7	0.71	M1	+2 °C	G (R290)	84.97	5,533
	170	IHC7	1.07	M1	+2 °C	G (R290)	93.73	6,658
	220	IHC7	1.43	M1	+2 °C	G (R290)	98.66	7,992
H140	120	IHC7	0.71	M1	+2 °C	G (R290)	89.64	5,861
	170	IHC7	1.07	M1	+2 °C	G (R290)	97.08	7,118
	220	IHC7	1.43	M1	+2 °C	G (R290)	98.92	8,583

Configuration: air cooled plug-in unit (R290) plexiglass sliding door closure, LED lighting, illuminated shelves

DIVA PAS*	RV 120	RV 170	RV 220			
External dimensions (LxDxH) H125	1176 x 1103 x 1257 mm	1671 x 1103 x 1257 mm	2166 x 1103 x 1257 mm			
External dimensions (LxDxH) H140	1176 x 1103 x 1408 mm	1671 x 1103 x 1408 mm	2166 x 1103 x 1408 mm			
Net weight H125	295 kg	375 kg	470 kg			
Net weight H140	318 kg	400 kg	492 kg			
Refrigeration	Ventilated					
Refrigerant	R290					
Climate class	3					
Operating conditions	25 °C / 60 %RH					
Product storage temperature	+1 / +10 °C					
Compressor (no type)	1 - Hermetic					
Defrost process	Off cycle					
Power supply voltage	230v / 50hz / 1ph					
Electrical input (nominal)	1350 w / 6.5 A	1620 w / 7.8 A	2120 w / 10.2 A			
Electrical input (defrost)	520 w / 2.8 A	490 w / 2.7 A	590 w / 3.2 A			





Taylor UK (a division of HTG Trading Ltd) 106 Claydon Business Park, Gt. Blakenham, Ipswich, Suffolk, IP6 ONL, United Kingdom

0800 838 896 - sales@taylor-company.co.uk www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification.