ISETTA ST/LX

Promotional ice cream cabinet



ITEM No.

Model options:

(ST - STRAIGHT GLASS)

□ISETTA RS ST TB 4

□ISETTA RS ST TB 6R

□ISETTA RS ST TB 7R

(LX - CURVED GLASS)

□ISETTA RS LX TB 4

□ISETTA RS LX TB 6R

□ISETTA RS LX TB 7R

Standard equipment:

Cool white LED lighting 5700 K° Front & side panels - White

Swivel castors with brake

Tilting panel on operators side

Optional extras:

□ 5 Lt standard Napoli pan (s/s)

☐4.75 Lt Napoli pan (S/S) (requires support kits)

■White cone holder

□Scoop wash (S/S)

□ Front sticker PM_AD1 - (call for details)



Features:

- ◆Promotional ice cream display with static refrigeration, finned evaporator and automatic electric defrosting.
- ◆A second level of standard 5 litre Napoli containers (120mm H) can be stored beneath the display level.
- ◆Models 6R and 7R are equipped with an additional refrigerated storage cell in the lower part of the cabinet.
- ◆One piece body structure with ecological polyurethane insulation (HCFC & HFC free) foamed with CO2.
- Interior and exterior in plasticised steel sheet.
- ◆Tempered glass structure, front glass available either straight (ST) or curved (LX) shape.
- •Rear pivoting methacrylate panel on operators side.
- ◆Work top in plasticised sheet with internal LED lighting.
- Built-in hermetic condensing unit with electronic control board.
- •Main structure in powder coated carbon steel.
- •Four pivoting wheels for easier handling.



ENERGY SAVING LED lights



INSTALLATION Plug-In



REFRIGERATION



ISO 14064



TEMPERATURE -16 / -14 °C



DEFROST Electric





REFRIGERANT R290











Taylor UK (a division of HTG Trading Ltd) 106 Claydon Business Park, Gt. Blakenham, Ipswich, Suffolk, IP6 ONL, United Kingdom

0800 838 896 - sales@taylor-company.co.uk www.taylor-company.co.uk


Due to continual research and development, these specifications are subject to change without notification.


ISETTA ST/LX





Promotional ice cream cabinet

Section view: (all dimensions in mm)









ISETTA ST/LX		Model type	Display area	Temp class	Reccom. temp	Energy class	Energy Efficiency	Annual Energy
Height	Length	турс	m ²	oluoo	°C	oluoo	Index	kWh/A
H117	82	IGF1	0.24	G3	-15 °C	B (R290)	17.50	2,062
	118	IGF2	0.36	G3	-15 °C	B (R290)	18.90	2,475
	135	IGF2	0.42	G3	-15 °C	B (R290)	19.40	2,665

Configuration: air cooled plug-in unit (R290) polycarbonate tilting panel closure, LED lighting

ISETTA ST/LX*	4	6R	7R			
External dimensions (LxDxH)	824 x 760 x 1176 mm	1184 x 800 x 1176 mm	1354 x 800 x 1176 mm			
Net weight	69 kg	97 kg	102 kg			
Refrigeration	Static					
Refrigerant	R290					
Climate class	7					
Operating conditions	35 °C / 75 %RH					
Product storage temperature	-16 / -14 °C					
Compressor (no type)	1 - Hermetic					
Defrost process	Electric					
Power supply voltage	230v / 50hz / 1ph					
Electrical input (nominal)	300 w / 2.4 A	460 w / 2.6 A	590 w / 4.1 A			
Electrical input (defrost)	810 w / 3.8 A					

ISO 14064









Taylor UK (a division of HTG Trading Ltd) 106 Claydon Business Park, Gt. Blakenham, Ipswich, Suffolk, IP6 ONL, United Kingdom

0800 838 896 - sales@taylor-company.co.uk www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification.

Napoli configuration:



5 Lt (STD) 360 x 165 x 120(h) mm

Model 4 Model 6R Model 7R Display Storage 4+(4)No 6+(6)Yes Yes 7+(7)



4.75 Lt

260 x 157 x 170(h) mm

Display Storage Model 4 6 No Model 6R 10 Yes Model 7R 11 Yes (Requires additional support kits - call for details)