KALEIDO PASTRY

Professional ventilated pastry display



ITEM No.

Model options:

□KALEIDO PAS RV 120 □KALEIDO PAS RV 170

□KALEIDO PAS RV 220

ALL models listed above are available either H117 or H135 high

Standard equipment:

Cool white LED lighting 5700 K° Work top - Glacier White Corian™ Front panel - Black back-painted glass Lower front grill - Grey (RAL9007) Side panels - Grey (RAL9007) lacquered Refrigerated glass shelf - 1 in H117, 2 in H135 Plexiglass sliding doors Swivel castors with brake & adjustable feet

Optional extras:

Self rolling night curtain

□RGB LED lighting behind front panel

☐ Remote refrigeration installation (call for details)

☐ Front panel finishes - Vetro Rosso Pelli Di Struzzo Alicrite

Features:

- ◆Pastry display case with ventilated refrigeration system with "FULL MODE" to also allow cooling of the shelves. One piece body insulated with ecological polyurethane (HCFC & HFC free) CO2 foam, 60 mm thick.
- Display deck tilted by 4°. Service shelf in corian and the operator's side rear panel in epoxy powder-coated carbon steel.
- Shelves adjustable in depth. Two refrigerated shelves in the H135 model and one shelf in the H117 model.
- ◆Double glazed heated front glass opens via top mounted hydraulic pistons. Aesthetic side panels made of laminate and lacquered on the lower part, double glazed heated glass on the upper section.
- ◆Interior lighting with LED strip on top and on each shelf.
- Structure base in, epoxy powder-coated carbon steel with adjustable feet and rotating castors.
- ◆Control panel with electronic control unit, located on lower part of operator's side and digital thermometer placed inside well.



ENERGY SAVING

LED lights + EC fan motor



REFRIGERATION Ventilated

ISO 14064



DEFROST Off cycle



REFRIGERANT R290



INSTALLATION

Plug-In / Remote (optional)



TEMPERATURE +1/+10°C



CLIMATE CLASS



ISO 9001









Taylor UK (a division of HTG Trading Ltd) 106 Claydon Business Park, Gt. Blakenham, Ipswich, Suffolk, IP6 ONL, United Kingdom

0800 838 896 - sales@taylor-company.co.uk www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification.

KALEIDO PASTRY




ITEM No.

Professional ventilated pastry display


Section view: (all dimensions in mm)

H117 1M: single shelf



H135

2M: two shelves



KALEIDO - PAS		Model type	Display area	Temp class	Reccom. temp	Energy class	Energy Efficiency	Annual Energy
Height	Length	турс	m ²	Ciuss	°C	Giuss	Index	kWh/A
H117	120	IVC4	1.29	Н	+6 °C	F (R290)	76.29	5,240
	170	IVC4	1.79	Н	+6 °C	F (R290)	75.39	6,302
	220	IVC4	2.29	Н	+6 °C	F (R290)	76.78	7,562
H135	120	IVC4	1.71	Н	+6 °C	F (R290)	68.48	5,568
	170	IVC4	2.34	Н	+6 °C	F (R290)	67.51	6,762
	220	IVC4	2.97	Н	+6 °C	F (R290)	68.51	8,154

Configuration: air cooled plug-in unit (R290) plexiglass sliding door closure, LED lighting, illuminated shelves

KALEIDO PAS*	RV 120	RV 170	RV 220			
External dimensions (LxDxH) H117	1182 x 1198 x 1182 mm	1677 x 1198 x 1182 mm	2172 x 1198 x 1182 mm			
External dimensions (LxDxH) H135	1182 x 1198 x 1362 mm	1677 x 1198 x 1362 mm	2172 x 1198 x 1362 mm			
Net weight H117	320 kg	409 kg	510 kg			
Net weight H135	346 kg	434 kg	535 kg			
Refrigeration	Ventilated					
Refrigerant	R452A					
Climate class	3					
Operating conditions	25 °C / 60 %RH					
Product storage temperature	+1 / +10 °C					
Compressor (no type)	1 - Hermetic					
Defrost process	Off cycle					
Power supply voltage	230v / 50hz / 1ph					
Electrical input (nominal)	1360 w / 7.4 A	1485 w / 8.1 A	1610 w / 8.7 A			
Electrical input (defrost)	420 w / 2.3 A	485 w / 2.6 A	450 w / 2.4 A			

ISO 14064









Taylor UK (a division of HTG Trading Ltd) 106 Claydon Business Park, Gt. Blakenham, lpswich, Suffolk, IP6 ONL, United Kingdom

0800 838 896 - sales@taylor-company.co.uk www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification.