

TORNADO 40

Upright fridge or freezer with glass door



Model 40 RS TB

Customisable area:

Model 40 - 580 x 162 h mm



Customisable area:

Model 40 - 620 x 1934 mm



ITEM No. _____

Model options:

(TB = LOW TEMPERATURE - FROZEN)

☐ **TORNADO 40 RS TB**

☐ **TORNADO 40 RV TB**

(TN = NORMAL TEMPERATURE - CHILLED)

☐ **TORNADO 40 RS TN**

☐ **TORNADO 40 RV TN**

*RS models have STATIC refrigeration and six fixed shelves

RV models have VENTILATED refrigeration and five adjustable shelves

Standard equipment:

5x Grids & supports - RV version ONLY

6x Fixed shelves - RS version ONLY

Cool white LED lighting 5700 K

External - White pre-painted sheet

Internal - White pre-painted sheet

Unidirectional runners with adjustable feet

Illuminated light box above door

Glass door with white surround

Optional extras:

☐ Additional grids & supports

Features:

- Upright glass fronted display cabinet available as either a fridge or freezer with static or ventilated refrigeration.
- One piece structure with ecological polyurethane insulation (HCFC & HFC free) foamed with CO2 - 60 mm thick.
- Internal and exterior base in white plasticised sheet. Door with silver coloured anodized aluminium frame and spring with decompression valve for frequent openings and large handle for an easier grip.
- Double LED lighting positioned along the sides of the door. Area illuminated ceiling light is positioned above the door.
- Main structure in carbon steel painted with epoxy powder with rollers for an easier handling and two adjustable feet.
- Control board with electronic board. Three kinds of defrosting: stop compressor defrosting in TN version, hot gas defrosting in RV TB and manual defrost on RS TB models. Drip tray with automatic evaporation system.
- The ventilated versions (RV) are fitted with adjustable side supports for grids. In the static versions RS TB, the shelves are fixed and act as evaporator and are painted with anti-corrosion treatment.



ENERGY SAVING
LED lights



REFRIGERATION
Static - RS
Ventilated - RV



DEFROST
Manual - RS TB
Hot gas - RV TB
Off Cycle - TN



REFRIGERANT
R290



INSTALLATION
Plug-In



TEMPERATURE
-1 / +5 °C - TN
-18 / -16 °C - TB



CLIMATE CLASS
4



ENERGY RATING
C - RS
D - RV



Sistema di Qualità
ISO 9001
Cert. CISQ/CSQ 9130.TAIF



Sistema di Qualità
ISO 14001
Cert. CIS ECO ISO 9191.ISA3



ISO 14064



Taylor UK
Catering Equipment Specialists

Taylor UK (a division of HTG Trading Ltd)

106 Claydon Business Park, Gt. Blakenham,
Ipswich, Suffolk, IP6 0NL, United Kingdom

0800 838 896 - sales@taylor-company.co.uk

www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification.

March 2021

TORNADO 40 - Glass fronted upright fridge or freezer - static or ventilated refrigeration

TORNADO 40




Upright fridge or freezer with glass door

ITEM No. _____


Section view: (all dimensions in mm)

40


RS TN





RV TN



RS TB



RV TB



TORNADO 40		Model type	Display area m ²	Temp class	Recomm. temp °C	Energy class	Energy Efficiency Index	Annual Energy kWh/A
H196 TN	40 RS 67	IVC4	0.67	L1	+2 °C	- (R290)	-	-
	40 RV 67	IVC4	0.61	L1	+2 °C	C (R290)	21.20	1,478
H196 TB	40 RS 67	IVF4	0.67	L1	-20 °C	C (R290)	27.60	2,263
	40 RV 67	IVF4	0.61	L1	-20 °C	D (R290)	38.20	2,957

Configuration: air cooled plug-in unit (R290) self closing swing door opening, LED lighting

TORNADO 40*	40 RS TN	40 RV TN	40 RS TB	40 RV TB
	CHILLED		FROZEN	
External dimensions (LxDxH)	670 x 675 x 1964 mm			
Capacity (gross/net)	400 / 285 Lt	400 / 260 Lt	400 / 285 Lt	400 / 265 Lt
Net weight	126 kg			
Refrigeration	Static	Ventilated	Static	Ventilated
Refrigerant	R290			
Climate class	4			
Operating conditions	30 °C / 55% RH			
Product storage temperature	-1 / +5 °C		-18 °C	-18 / -16 °C
Compressor (no. - type)	1 - Hermetic			
Defrost process	Off cycle		Manual	Hot gas
Power supply voltage	230v / 50hz / 1ph			
Electrical input (nominal)	400 w / 2.2 A	430 w / 2.3 A	700 w / 4.5 A	530 w / 3.8 A
Electrical input (defrost)	120 w / 0.7 A	110 w / 0.7 A	-	840 w / 4.8 A



ISO 9001
Cert. CISO/CISO 9130.TAIF



ISO 14001
Cert. CISO/CISO 9191.ISA3



ISO 14064



Taylor UK
Catering Equipment Specialists

Taylor UK (a division of HTG Trading Ltd)
106 Claydon Business Park, Gt. Blakenham,
Ipswich, Suffolk, IP6 0NL, United Kingdom
0800 838 896 - sales@taylor-company.co.uk
www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification.

*Data for air cooled units. Water cooled and remote installations are available on request.

March 2021

TORNADO 40 - Glass fronted upright fridge or freezer - static or ventilated refrigeration

TORNADO 50

Upright fridge or freezer with glass door



Model 50 RV TB with one additional grid

Customisable area:

Model 50 - 1250 x 162 h mm



Customisable area:

Model 50 - 770 x 1934 mm

ITEM No. _____

Model options:

(TB = LOW TEMPERATURE - FROZEN)

☐ TORNADO 50 RV TB

(TN = NORMAL TEMPERATURE - CHILLED)

☐ TORNADO 50 RV TN

*RV models have VENTILATED refrigeration and five adjustable shelves

Standard equipment:

5x Grids & supports

Cool white LED lighting 5700 K°

External - White pre-painted sheet

Internal - White pre-painted sheet

Unidirectional runners with adjustable feet

Illuminated light box above door

Glass door with white surround

Optional extras:

☐ Additional grids & supports

Features:

- Upright glass fronted display cabinet available as either a fridge or freezer with static or ventilated refrigeration.
- One piece structure with ecological polyurethane insulation (HCFC & HFC free) foamed with CO2 - 60 mm thick.
- Internal and exterior base in white plasticised sheet. Door with silver coloured anodized aluminium frame and spring with decompression valve for frequent openings and large handle for an easier grip.
- Double LED lighting positioned along the sides of the door. Area illuminated ceiling light is positioned above the door.
- Main structure in carbon steel painted with epoxy powder with rollers for an easier handling and two adjustable feet.
- Control board with electronic board. Two kinds of defrosting: stop compressor defrosting in TN version and hot gas defrosting in TB models. Drip tray with automatic evaporation system.



ENERGY SAVING
LED lights



REFRIGERATION
Ventilated - RV



DEFROST
Off cycle - TN
Hot gas - TB



REFRIGERANT
R290



INSTALLATION
Plug-In



TEMPERATURE
-1 / +5 °C - TN
-18 / -16 °C - TB



CLIMATE CLASS
4



ENERGY RATING
C - TN
D - TB



Sistema di Qualità
ISO 9001
Cert. CISQ/CSQ 9130.TAIF



Sistema di Qualità
ISO 14001
Cert. CIS ECO ISO 9191.ISA3



ISO 14064



TaylorUK
Catering Equipment Specialists

Taylor UK (a division of HTG Trading Ltd)

106 Claydon Business Park, Gt. Blakenham,
Ipswich, Suffolk, IP6 0NL, United Kingdom

0800 838 896 - sales@taylor-company.co.uk

www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification.

March 2021

TORNADO 50 - Glass fronted upright fridge or freezer - ventilated refrigeration

TORNADO 50




Upright fridge or freezer with glass door

ITEM No. _____

Section view: (all dimensions in mm)

50



TORNADO 50		Model type	Display area m ²	Temp class	Recomm. temp °C	Energy class	Energy Efficiency Index	Annual Energy kWh/A
Height	Length							
H196 TN	50 RV 67	IVC4	0.63	L1	+2 °C	C (R290)	22.20	1,478
H196 TB	50 RV 67	IVF4	0.62	L1	-20 °C	D (R290)	39.30	3,066

Configuration: air cooled plug-in unit (R290) self closing swing door opening, LED lighting

TORNADO 50*	50 RV TN	50 RV TB
	CHILLED	FROZEN
External dimensions (LxDxH)	670 x 825 x 1964 mm	
Capacity (gross/net)	530 / 335 Lt	
Net weight	151 kg	
Refrigeration	Ventilated	
Refrigerant	R290	
Climate class	4	
Operating conditions	30 °C / 55% RH	
Product storage temperature	-1 / +5 °C	-18 / -16 °C
Compressor (no. - type)	1 - Hermetic	
Defrost process	Off cycle	Hot gas
Power supply voltage	230v / 50hz / 1ph	
Electrical input (nominal)	520 w / 2.8 A	750 w / 2.7 A
Electrical input (defrost)	140 w / 0.8 A	1170 w / 4.0 A



Taylor UK (a division of HTG Trading Ltd)
 106 Claydon Business Park, Gt. Blakenham,
 Ipswich, Suffolk, IP6 0NL, United Kingdom
0800 838 896 - sales@taylor-company.co.uk
www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification.

*Data for air cooled units. Water cooled and remote installations are available on request.

TORNADO 100

Glass fronted double door fridge, freezer or combination



Model 100 RV TB

ITEM No. _____

Model options:

(TB = LOW TEMPERATURE - FROZEN)

☐ **TORNADO 100 RV TB+TB**

(TN = NORMAL TEMPERATURE - CHILLED)

☐ **TORNADO 100 RV TN+TN**

(TB+TN = COMBINATION TEMPERATURE - CHILLED/FROZEN)

☐ **TORNADO 100 RV TB+TN**

*RV models have VENTILATED refrigeration and five adjustable shelves per section.

Standard equipment:

5+5 x Grids & supports

Cool white LED lighting 5700 K°

External - White pre-painted sheet

Internal - White pre-painted sheet

Unidirectional runners with adjustable feet

Illuminated light box above door

Glass door with white surround

Optional extras:

☐ Additional grids & supports

Customisable area:

Model 100 - 1250 x 162 h mm



Customisable area:

Model 100 - 770 x 1934 mm

Features:

- ♦ Upright glass fronted display cabinet available as either a fridge or freezer with static or ventilated refrigeration.
- ♦ One piece structure with ecological polyurethane insulation (HCFC & HFC free) foamed with CO2 - 60 mm thick.
- ♦ Internal and exterior base in white plasticised sheet. Door with silver coloured anodized aluminium frame and spring with decompression valve for frequent openings and large handle for an easier grip.
- ♦ Double LED lighting positioned along the sides of the door. Area illuminated ceiling light is positioned above the door.
- ♦ Main structure in carbon steel painted with epoxy powder with rollers for an easier handling and two adjustable feet.
- ♦ Control board with electronic board. Two kinds of defrosting: stop compressor defrosting in TN version and hot gas defrosting in TB models. Drip tray with automatic evaporation system.



ENERGY SAVING
LED lights



REFRIGERATION
Ventilated - RV



DEFROST
Hot gas - TB
Off Cycle - TN



REFRIGERANT
R290



INSTALLATION
Plug-In



TEMPERATURE
-1 / +5 °C - TN
-18 / -16 °C - TB



CLIMATE CLASS
4



ENERGY RATING
C - TN+TN
E - TB+TB



Sistema di Qualità
ISO 9001
Cert. CISQ/CSQ 9130.TAIF



Sistema di Qualità
ISO 14001
Cert. CIS ECO ISO 9191.ISA3



ISO 14064



Taylor UK
Catering Equipment Specialists

Taylor UK (a division of HTG Trading Ltd)

106 Claydon Business Park, Gt. Blakenham,
Ipswich, Suffolk, IP6 0NL, United Kingdom

0800 838 896 - sales@taylor-company.co.uk

www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification.

March 2021

TORNADO 100 - Glass fronted double door fridge, freezer or combination - ventilated refrigeration

TORNADO 100



Glass fronted double door fridge, freezer or combination


ITEM No. _____

Section view: (all dimensions in mm)

100

RV TN

RV TB



TORNADO 100		Model type	Display area m ²	Temp class	Recomm. temp °C	Energy class	Energy Efficiency Index	Annual Energy kWh/A
Height	Length							
H196	TN+TN 134	IVC4	1.32	4	+2 °C	C (R290)	34.70	3,373
	TB+TN 134	IVF4	1.22	L1	-20 °C	D (R290)	40.50	5,058
	TB+TB 134	IVF4	1.22	L1	-20 °C	E (R290)	64.30	8,030

Configuration: air cooled plug-in unit (R290) self closing swing door opening, LED lighting

TORNADO 100*		100 RV TN+TN	100 RV TB+TB	100 RV TB+TN
		CHILLED	FROZEN	CHILLED + FROZEN
External dimensions (LxDxH)		1340 x 825 x 1964 mm		
Capacity (gross/net)		10600 / 670 ltr		
Net weight		295 kg		
Refrigeration		Ventilated		
Refrigerant		R290		
Climate class		4		
Operating conditions		30 °C / 55% RH		
Product storage temperature		-1 / +5 °C	-18 / -16 °C	(TB) -18 / -16 °C (TN) -1 / +5 °C
Compressor (no. - type)		2 - Hermetic		
Defrost process		Off cycle	Hot gas	Hot gas / Off cycle
Power supply voltage		230v / 50hz / 1ph		
Electrical input (nominal)		750 w / 4.1 A	1740 w / 8.6 A	1650 w / 8.9 A
Electrical input (defrost)		160 w / 1.0 A	2840 w / 13.4 A	1850 w / 10.0 A



Taylor UK
Catering Equipment Specialists

Taylor UK (a division of HTG Trading Ltd)
106 Claydon Business Park, Gt. Blakenham,
Ipswich, Suffolk, IP6 0NL, United Kingdom
0800 838 896 - sales@taylor-company.co.uk
www.taylor-company.co.uk

Due to continual research and development, these specifications are subject to change without notification.

*Data for air cooled units. Water cooled and remote installations are available on request.

March 2021

TORNADO 100 – Glass fronted double door fridge, freezer or combination – ventilated refrigeration