



PL412M31G0 - FriFri Precision 412 Electric Free-standing Single Tank Fryer - 2 Baskets -W 400 mm - 18.0 kW For the chef who wants superb temperature control for consistently excellent results, a free standing Precision 412 is the fryer of choice.

- Electronic temperature control and powerful elements maintains oil to within +/-1°C of the temperature selected, reducing oil usage and ensuing your food always has that all-important crunch.
- With one cooking programme, perfect for when you want to cook the same product time after time, to the same exacting standards.
- Digital timer displays the count down, with a buzzer sounding at the end of the cook cycle.
- Temperature view shows current oil temperature, enabling you to make an informed decision as to when to start cooking.

- Are there more fries than last time? Adaptive cooking automatically adjusts the cooking times to suit your batch size ensuring you never serve undercooked food.
- Keeping your oil in peak condition! Optional xFri@ filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes – so easy there is no excuse not to!
- Raising food to the next level. Perfect for kitchens where you don't have time for constant supervision, optional LiftFri® automatic basket lifting system lifts food at the end of the cycle to prevent overcooking.
- Pressed tank for strength and durability.
 Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.

Summary		Power and Performance	
Brand	FriFri	Total Power kW	18.0
Range	Precision	Temperature Range °C	60-190
Power Type	Electric	IP Rating	IPX4
Init Type	Free-standing	Temperature Control	Electronic
Available in UK Only	No		
JK Warranty	2 Years Parts and Labour Warranty		
xport Warranty	Contact your local dealer		
TIN	5056105122272		
Key Specifications		Capacity	
lumber of Baskets	2	Product Output per Hour	40kg fries - 7mm[frozen]
lumber of Tanks	1	Capacity Litres	17.0-20.5
ravity Filtration	Yes		
umped Filtration	No		
rain Location	Through the body		





Weights and Dimensions		Supply Connections	
Unit Height (External) mm	994	Requires Installation	Yes
Unit Width (External) mm	397.5	Requires Electrical Supply	Yes
Unit Depth (External) mm	650	UK 3 Pin Plug	No
Net Weight Kg	63	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	18,000
		Three Phase Amps	L1=26.1; L2=26.1; L3=26.1
		Three Phase Voltage	400
		Number of Supply Cables	1

Shipping

Packed Weight Kg69.5Packed Height cm113Packed Width cm79Packed Depth cm52

Available Options

Oil Pump

OP1 10il Pump

Basket Lift

OL1 1 Basket Lift

Baskets

411_1_BASKET 1 Basket
411_2_BASKETS 2 Baskets

Legs/Castors

 OC200
 0C200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front]

 OC400
 0C400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]

Available Accessories

FZ411048 LARGE BASKET FOR 411 - 5MM MESH - COMPLETE WITH HANDLE





TAYLOR UK

106 Claydon Business Park, Gt. Blakenham, Ipswich, Suffolk, IP6 0NL

Tel: **01473 350046**

Email: sales@taylor-company.co.uk Web: www.taylor-company.co.uk