



SL422L32G0 - FriFri Super Easy 422 Electric Free-standing Twin Tank Fryer with Filtration - 2 Baskets - W 400 mm - 2 x 7.5 kW

When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A free standing Super Easy 422 offers outstanding value with no compromise in quality or performance.

- Outstanding quality with no compromise in quality or performance.
- Mechanical thermostat maintains oil to within +/-8 °C of the temperature selected.
- Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- Keeping your oil in peak condition! Integral gravity filtration extends oil life by up to $75\,\%$ saving you money on oil purchase and disposal costs. Optional xFri® filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes - so easy there is no excuse not to!
- Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- Optimum Allergy Control. Supplied with separate oil buckets, and can be supplied with separate pumped filtration systems, providing completely segregated gravity filtration for optimum allergen control or to cater for dietary preferences.

Drain Location

Specifications			
Summary		Power and Performance	
Brand	FriFri	Total Power kW	2×7.5
Range	Super Easy	Temperature Range °C	95-190
Power Type	Electric	IP Rating	IPX4
Unit Type	Free-standing	Temperature Control	Mechanical
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105123613		
Key Specifications		Capacity	
Number of Baskets	2	Product Output per Hour	2 x 17kg fries - 7mm [frozen]
Number of Tanks	2	Capacity Litres	2×7.5-9.0
Gravity Filtration	Yes		
Pumped Filtration	No		

Through the body





Weights and Dimensions		Supply Connections	
Unit Height (External) mm	986	Requires Installation	Yes
Unit Width (External) mm	397.5	Requires Electrical Supply	Yes
Unit Depth (External) mm	650	UK 3 Pin Plug	No
Net Weight Kg	54.7	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	2 x 7,500
		Three Phase Amps	L1=2 x 10.9; L2=2 x 10.9; L3=2 x 10.9
		Three Phase Voltage	400
		Number of Supply Cables	2
		Number of Supply Cables	2

Shipping

Packed Weight Kg 60.17 Packed Height cm 113 Packed Width cm 79 Packed Depth cm 52

Available Options

Oil Pump

OP1 10il Pump OP2 2 Oil Pumps

Legs/Castors

OC200 OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front] OC400 OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]





TAYLOR UK

Web: www.taylor-company.co.uk

Print Date: 11/05/2023 Product Code: SL422L32G0 Page Number: 2